

12/21/98



10571 U.S. PTO

A



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of: Mark Rapaich

Title: DIGITAL YUV VIDEO EQUALIZATION AND GAMMA CORRECTION

Attorney Docket No.: 450.221US1

PATENT APPLICATION TRANSMITTAL

BOX PATENT APPLICATION

Assistant Commissioner for Patents

Washington, D.C. 20231

We are transmitting herewith the following attached items and information (as indicated with an "X"):

- ☒ Utility Patent Application under 37 CFR § 1.53(b) comprising:
- ☒ Specification (10 pgs, including claims numbered 1 through 11 and a 1 page Abstract).
 - ☒ Formal Drawing(s) (2 sheets).
 - ☒ Signed Combined Declaration and Power of Attorney (3 pgs).
- ☒ Assignment of the invention to Gateway 2000, Inc. (2 pgs) and Recordation Form Cover Sheet.
- ☒ Return postcard.

The filing fee will be calculated as follows:

	No. Filed	No. Extra	Rate	Fee
TOTAL CLAIMS	11 - 20 =	0	x 18 =	\$0.00
INDEPENDENT CLAIMS	3 - 3 =	0	x 78 =	\$0.00
] MULTIPLE DEPENDENT CLAIMS PRESENTED				\$0.00
BASIC FEE				\$760.00
TOTAL				\$760.00

PLEASE CHARGE THE FILING FEE OF \$760.00 AND THE ASSIGNMENT RECORDATION FEE OF \$40.00 TO DEPOSIT ACCOUNT 50-0439.

SCHWEGMAN, LUNDBERG, WOESSNER & KLUTH, P.A.
P.O. Box 2938, Minneapolis, MN 55402 (612-373-6900)

Customer Number **21186**By: Daniel J. Polglaze

Atty: Daniel J. Polglaze

Reg. No. 39,801

"Express Mail" mailing label number: EL106841253USDate of Deposit: December 21, 1998

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.

By: Chris HammondSignature: Chris Hammond

Digital YUV Video Equalization and Gamma Correction

Field of the Invention

The present invention relates to video equalization and gamma correction in computer systems and in particular to video equalization and gamma correction of digital YUV video signals.

Background

Cathode ray tubes, CRTs, are made with electron guns which emit electrons that are guided by electromagnetic fields to provide a picture on a screen. It has been long known that CRTs do not produce a light intensity proportional to the input voltage controlling the strength of the electron gun emissions. Instead, the intensity produced by a CRT is proportional to the input voltage raised by a power of a value referred to as gamma. The value of gamma varies depending on the CRT, but is typically close to 2.5. Projecting an image that is not distorted in contrast therefore requires correcting the intensity voltage provided to the electron guns of the CRT by a power of gamma.

Most sensors used in television cameras produce output voltages proportional to image intensity. A correction for CRT gamma must be applied to the camera signal at some point before the image is displayed on a CRT. Television standards include an initial gamma correction of 0.45 applied in the television camera, to compensate for both the CRT gamma of 2.5 and the apparent reduction in contrast when a TV is viewed against the dim background typically found in a living room.

Many computer displays ignore the effects of CRT monitor or display gamma. Digital video information is converted linearly into voltages that drive the CRT in the display. The digital image intensity values in the frame buffer are therefore not proportional to the resulting display intensity. For example, a digital value of one half the maximum in the frame buffer will result in a displayed intensity less than one half maximum display intensity.

Some displays include hardware lookup tables that correct for monitor gamma. In these systems, digital RGB frame buffer values provided by the system are corrected for

gamma by the CRT by means of a lookup table in the display controller, producing a display system gamma of 1.0 that linearly maps frame buffer values into displayed intensity. In US patent No. 5,589,889 to Kawaoka, gamma lookup tables are set by means of a processor for both a desired video source and for a desired display device.

5 While gamma correction is widely provided for video information within personal computers in the digital RGB color space, it is not currently provided for digital information in the YUV color space. RGB encoded digital video consists of three digital values, each value representing an intensity level for red, green, or blue color. Application of gamma to such a signal involves simple mathematical alteration of these
10 intensity signals to produce corresponding corrected intensity signals.

Digital video in the YUV color space involves encoding of luminance (Y) and chrominance (UV) information in digital form. The UV component represents a point on a two-dimensional color space, such that differences in UV values are proportional to perceived color differences. Application of gamma correction to such a signal involves
15 either conversion to the RGB color space before gamma correction or application of more complex mathematical algorithms than are needed in the RGB color space. Gamma correction of YUV signals is therefore computationally much more demanding if corrected in the YUV color space, so digital gamma correction of digital YUV signals is typically done after conversion to the RGB color space. There is a need to apply gamma
20 correction to digital YUV signals in personal or general purpose computers without converting the signal to digital RGB as a necessary step in performing the gamma correction.

Summary

25 Gamma correction, color saturation, tint, brightness, and contrast correction are provided for digital YUV signals. Such correction is performed via application of algorithms to a digital YUV video stream.

In one embodiment, a processor applies an algorithm to the digital YUV signal and is incorporated into video hardware in a personal computer. The video hardware
30 receives a digital YUV signal from a source such as a DVD player. The algorithm is

empirically determined in one embodiment for the type of display device used to display the signal. The algorithm comprises a least-squares fit polynomial equation or a lookup table. The video hardware then corrects the displayed intensity by applying one or more corrections such as gamma correction, color saturation, tint, brightness, or contrast correction.

In a further embodiment, gamma, color saturation, tint, brightness, and contrast correction may be digitally controlled by software that allows a user to set the correction factors such as the gamma correction factor. The video hardware then applies this user-specified correction factor to the video signal through digital processing.

In another embodiment, the video hardware may receive video encoded with a gamma correction factor. The gamma correction factor is then compensated for by applying gamma correction needed for other video components such as a CRT, and result in a displayed image that is displayed with the proper gamma for both the video source and display.

Description of the Figures

Figure 1 is a block diagram of a typical computer system in accordance with the present invention.

Figure 2 is a diagram illustrating the display intensity produced by different electron gun voltages in a typical CRT, both with and without gamma correction.

Figure 3 is a block diagram showing incorporation of a digital processor that may be used to correct digital YUV signals for gamma, color saturation, tint, brightness and contrast.

Detailed Description

In the following description, reference is made to the accompanying drawings, which form a part of this description and show by way of illustration specific embodiments in which the invention may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention. Other embodiments may also be utilized to practice the invention, and structural, logical, and

electrical changes may be made without departing from the scope of the present invention. The following description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is defined by the appended claims.

Figure 1 shows a block diagram of a computer system 100 according to the present invention. In this embodiment, processor 102, system controller 112, cache 114, and data-path chip 118 are each coupled to host bus 110. Processor 102 is a microprocessor such as a 486-type chip, a Pentium®, Pentium II® or other suitable microprocessor. Cache 114 provides high-speed local-memory data (in one embodiment, for example, 512 kB of data) for processor 102, and is controlled by system controller 112, which loads cache 114 with data that is expected to be used soon after the data is placed in cache 112 (i.e., in the near future). Main memory 116 is coupled between system controller 114 and data-path chip 118, and in one embodiment, provides random-access memory of between 16 MB and 128 MB of data. In one embodiment, main memory 116 is provided on SIMMs (Single In-line Memory Modules), while in another embodiment, main memory 116 is provided on DIMMs (Dual In-line Memory Modules), each of which plugs into suitable sockets provided on a motherboard holding many of the other components shown in Figure 1. Main memory 116 includes standard DRAM (Dynamic Random-Access Memory), EDO (Extended Data Out) DRAM, SDRAM (Synchronous DRAM), or other suitable memory technology. System controller 112 controls PCI (Peripheral Component Interconnect) bus 120, a local bus for system 100 that provides a high-speed data path between processor 102 and various peripheral devices, such as graphics devices, storage drives, network cabling, etc. Data-path chip 118 is also controlled by system controller 112 to assist in routing data between main memory 116, host bus 110, and PCI bus 120.

In one embodiment, PCI bus 120 provides a 32-bit-wide data path that runs at 33 MHZ. In another embodiment, PCI bus 120 provides a 64-bit-wide data path that runs at 33 MHZ. In yet other embodiments, PCI bus 120 provides 32-bit-wide or 64-bit-wide data paths that runs at higher speeds. In one embodiment, PCI bus 120 provides connectivity to I/O bridge 122, graphics controller 127, and one or more PCI connectors 121 (i.e., sockets into which a card edge may be inserted), each of which accepts a

standard PCI card. In one embodiment, I/O bridge 122 and graphics controller 127 are each integrated on the motherboard along with system controller 112, in order to avoid a board-connector-board signal-crossing interface and thus provide better speed and reliability. In the embodiment shown, graphics controller 127 is coupled to a video memory 128 (that includes memory such as DRAM, EDO DRAM, SDRAM, or VRAM (Video Random-Access Memory)), and drives VGA (Video Graphics Adaptor) port 129. VGA port 129 can connect to industry-standard monitors such as VGA-type, SVGA (Super VGA)-type, XGA-type (eXtended Graphics Adaptor) or SXGA-type (Super XGA) display devices. Other input/output (I/O) cards having a PCI interface can be plugged into PCI connectors 121.

In one embodiment, I/O bridge 122 is a chip that provides connection and control to one or more independent IDE connectors 124-125, to a USB (Universal Serial Bus) port 126, and to ISA (Industry Standard Architecture) bus 130. In this embodiment, IDE connector 124 provides connectivity for up to two standard IDE-type devices such as hard disk drives, CDROM (Compact Disk-Read-Only Memory) drives, DVD (Digital Video Disk) drives, or TBU (Tape-Backup Unit) devices. In one similar embodiment, two IDE connectors 124 are provided, and each provide the EIDE (Enhanced IDE) architecture. In the embodiment shown, SCSI (Small Computer System Interface) connector 125 provides connectivity for up to seven or fifteen SCSI-type devices (depending on the version of SCSI supported by the embodiment). In one embodiment, I/O bridge 122 provides ISA bus 130 having one or more ISA connectors 131 (in one embodiment, three connectors are provided). In one embodiment, ISA bus 130 is coupled to I/O controller 152, which in turn provides connections to two serial ports 154 and 155, parallel port 156, and FDD (Floppy-Disk Drive) connector 157. In one embodiment, ISA bus 130 is connected to buffer 132, which is connected to X bus 140, which provides connections to real-time clock 142, keyboard/mouse controller 144 and keyboard BIOS ROM (Basic Input/Output System Read-Only Memory) 145, and to system BIOS ROM 146.

Figure 1 shows one exemplary embodiment of the present invention, however other bus structures and memory arrangements are specifically contemplated.

A diagram representing the nonlinearity between voltage input and display intensity in CRTs is shown in Figure 2. A straight line 203 represents a curve wherein an incremental increase in video signal voltage creates a proportional increase in displayed output intensity. This curve represents the ideal video display system response, but is not characteristic of typical CRTs. A curve 201 illustrates that for relatively small voltage inputs, a typical CRT does not produce a proportional increase in displayed image intensity, but instead remains somewhat darker. Most CRTs have a gamma of about 2.5, requiring input voltage compensation by raising the input voltage to the power gamma to transform the uncorrected CRT response curve 201 into a perceived linear eye response curve also represented by curve 203. The factor by which the uncorrected CRT response curve 201 must be altered is displayed in the gamma compensation curve 202. This gamma compensation curve represents the response characteristics needed by a gamma correction circuit, such that small values of video signal input voltage provided to the gamma correction circuit result in an output that is proportionately larger than the input voltage.

Figure 3 shows a portion of a computer system comprising the components of a digital YUV signal equalization apparatus. A digital YUV video signal 302 is provided by a digital YUV video source 301, and received by a digital processor 303. In one embodiment, the processor may be a commercially available digital signal processor programmed with mathematical algorithms to correct video distortions in the YUV video signal. In a further embodiment, the mathematical algorithm comprises an empirically determined least squares fit polynomial equation, determined for each display device. The algorithm comprises a lookup table having gamma values similarly determined at each of a plurality of signal levels dependent upon display device characteristics.

In another embodiment, the processor 303 corrects one or more digital YUV signal distortions selected from the group consisting of gamma correction, color saturation, tint, brightness and contrast. The processor outputs a corrected signal 304, that may be provided to a CRT or other display 305. The corrected signal 304 may be corrected for gamma, or equalized for color saturation, tint, brightness, or contrast, or any combination thereof. The display 305 then produces an image 306, corrected for the

gamma properties of display 305 or other signal distortions.

The video source 301 may consist of any video source that produces a digital YUV signal, such as DVD, MPEG, CVD, CD, satellite broadcast, and NTSC digital video signals. In the preferred embodiment, the corrective algorithms processor 303
5 applies to the digital YUV signal 302 are implemented by software running on the personal computer or by a combination of software and hardware, so that a user may specify parameters of the algorithms and therefore control the degree of correction performed by the processor.

It is to be understood that the above description is intended to be illustrative, and
10 not restrictive. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The scope of the invention should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled.

What is claimed is:

1. A personal computer system comprising:
 - a video source capable of providing a digital YUV video signal;
 - a video output capable of connecting to a video display device;
 - a digital processor employing a corrective algorithm that corrects the digital YUV signal provided by the video source and provides a corrected signal to the video output.
2. The personal computer of claim 1 where the correction is selected from the group consisting of gamma correction, color saturation correction, tint correction, brightness correction and contrast correction.
3. The personal computer system of claim 1, further comprising a software module for user configuration of the digital processor that corrects the digital YUV signal.
4. The personal computer system of claim 1, wherein the video sources comprise multiple sources selected from the group consisting of MPEG, NTSC, CVD, CD and satellite broadcast digital video signals.
5. The personal computer system of claim 2, wherein the digital YUV video signal is encoded with a correction factor that is compensated for in applying the corrective algorithms to the digital YUV signal.
6. A process comprising the steps of:
 - receiving a YUV digital video signal;
 - correcting the digital YUV signal within a personal computer; and
 - providing a corrected digital YUV signal to an output for connection to a display device.


7. The process of claim 6 where the correction is selected from the group consisting of gamma correction, color saturation correction, tint correction, brightness correction and contrast correction.
8. The process of claim 6, further comprising a step of configuration of a software module that configures the digital signal processor that corrects the digital YUV signal.
9. The process of claim 6, wherein the received YUV digital video signal is provided by video sources selected from the group consisting of MPEG, NTSC, CVD, CD and satellite broadcast digital video signals.
10. The process of claim 6, wherein the received digital YUV video signal is encoded with a correction factor that is compensated for in correcting the digital YUV signal.
11. A personal computer system comprising:
- a processor;
 - a bus;
 - main memory;
 - a system controller;
 - a graphics controller;
 - a video source capable of providing a digital YUV video signal;
 - a video output capable of connecting to a video display device; and
 - a digital processor that corrects the digital YUV signal provided by the video source and provides a corrected signal to the video output.

Abstract

Gamma correction, color saturation, tint, brightness, and contrast correction are provided for digital YUV signals by use of video hardware or software in a personal computer. The video hardware receives a digital YUV signal from a source such as a DVD player. An algorithm is empirically determined for the type of display device used to display the signal. A least-squares fit polynomial equation or a lookup table is used to determine a correction for displayed intensity by applying one or more corrections such as gamma correction, color saturation, tint, brightness, or contrast correction. The resulting image is displayed with the proper gamma for both video source and display.

*Express Mail" mailing label number: EL106841253US
Date of Deposit: DEC. 21, 1990
I hereby certify that this paper or fee is being deposited with the
United States Postal Service "Express Mail Post Office Addressee"
service under 37 CFR 1.10 on the date indicated above and is
addressed to the Assistant Commissioner for Patents,
Washington, D.C. 20231
Printed Name: CHRIS HAMMOND
Signature: Chris Hammond

FIG. 1






FIG. 2




FIG. 3

United States Patent Application

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor I hereby declare that: my residence, post office address and citizenship are as stated below next to my name; that

I verily believe I am the original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled: MULTIPLE AUDIO AND VIDEO SIGNAL ROUTING WITH PC COMPATIBILITY.

The specification of which is attached hereto.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56 (see page 3 attached hereto).

I hereby claim foreign priority benefits under Title 35, United States Code, §119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on the basis of which priority is claimed:

No such applications have been filed.

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below.

No such applications have been filed.

I hereby claim the benefit under Title 35, United States Code, § 120/365 of any United States and PCT international application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

No such applications have been filed.

I hereby appoint the following attorney(s) and/or patent agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith:

Anglin, J. Michael	Reg. No. 24,916	Fogg, David N.	Reg. No. 35,138	Litman, Mark A.	Reg. No. 26,390
Arora, Suneel	Reg. No. 42,267	Forrest, Bradley A.	Reg. No. 30,837	Lundberg, Steven W.	Reg. No. 30,568
Bianchi, Timothy E.	Reg. No. 39,610	Hale, Jeffrey D.	Reg. No. 40,012	Mates, Robert E.	Reg. No. 35,271
Billion, Richard E.	Reg. No. 32,836	Harris, Robert J.	Reg. No. 37,346	McCrackin, Ann M.	Reg. No. 42,858
Black, David W.	Reg. No. 42,331	Holloway, Sheryl S.	Reg. No. 37,850	Padys, Danny J.	Reg. No. 35,635
Brennan, Thomas F.	Reg. No. 35,075	Huebsch, Joseph C.	Reg. No. 42,673	Polglaze, Daniel J.	Reg. No. 39,801
Brooks, Edward J., III	Reg. No. 40,925	Kalis, Janal M.	Reg. No. 37,650	Schwegman, Micheal L.	Reg. No. 25,816
Claiborne, Anthony	Reg. No. 39,636	Klima-Silberg, Catherine I.	Reg. No. 40,052	Sieffert, Kent J.	Reg. No. 41,312
Clark, Barbara J.	Reg. No. 38,107	Kluth, Daniel J.	Reg. No. 32,146	Slifer, Russell D.	Reg. No. 39,838
Drake, Eduardo E.	Reg. No. 40,594	Lacy, Rodney L.	Reg. No. 41,136	Terry, Kathleen R.	Reg. No. 31,884
Dryja, Michael A.	Reg. No. 39,662	Leffert, Thomas W.	Reg. No. 40,697	Viksnins, Ann S.	Reg. No. 37,748
Embretson, Janet E.	Reg. No. 39,665	Lemaire, Charles A.	Reg. No. 36,198	Woessner, Warren D.	Reg. No. 30,440

I hereby authorize them to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/organization/who/which first sends/sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct Schwegman, Lundberg, Woessner & Kluth, P.A. to the contrary.

Please direct all correspondence in this case to Schwegman, Lundberg, Woessner & Kluth, P.A. at the address indicated below:

P.O. Box 2938, Minneapolis, MN 55402

Telephone No. (612)373-6900

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of sole inventor : **Mark Rapaich**
Citizenship: **United States of America** Residence: **Westfield, IA**
Post Office Address: **23176 Concord Avenue**
Westfield, IA 51062

Signature:  Date: 12/12/98
Mark Rapaich

Full Name of inventor:
Citizenship: Residence:
Post Office Address:

Signature: _____ Date: _____

Full Name of inventor:
Citizenship: Residence:
Post Office Address:

Signature: _____ Date: _____

Full Name of inventor:
Citizenship: Residence:
Post Office Address:

Signature: _____ Date: _____

§ 1.56 Duty to disclose information material to patentability.

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is canceled or withdrawn from consideration, or the application becomes abandoned. Information material to the patentability of a claim that is canceled or withdrawn from consideration need not be submitted if the information is not material to the patentability of any claim remaining under consideration in the application. There is no duty to submit information which is not material to the patentability of any existing claim. The duty to disclose all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by §§ 1.97(b)-(d) and 1.98. However, no patent will be granted on an application in connection with which fraud on the Office was practiced or attempted or the duty of disclosure was violated through bad faith or intentional misconduct. The Office encourages applicants to carefully examine:

- (1) prior art cited in search reports of a foreign patent office in a counterpart application, and
- (2) the closest information over which individuals associated with the filing or prosecution of a patent application believe any pending claim patentably defines, to make sure that any material information contained therein is disclosed to the Office.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and

- (1) It establishes, by itself or in combination with other information, a prima facie case of unpatentability of a claim; or
- (2) It refutes, or is inconsistent with, a position the applicant takes in:
 - (i) Opposing an argument of unpatentability relied on by the Office, or
 - (ii) Asserting an argument of patentability.

A prima facie case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

(c) Individuals associated with the filing or prosecution of a patent application within the meaning of this section are:

- (1) Each inventor named in the application;
- (2) Each attorney or agent who prepares or prosecutes the application; and
- (3) Every other person who is substantively involved in the preparation or prosecution of the application and who is associated with the inventor, with the assignee or with anyone to whom there is an obligation to assign the application.

(d) Individuals other than the attorney, agent or inventor may comply with this section by disclosing information to the attorney, agent, or inventor.